



EAZY Wood Composite Decking

*easy maintenance pre-finished surface with timber look
termite & water resistant (manufacturer warranty)*

Typical Components of EAZYWOOD WPC Decking System



Component	Detailed dimensions (mm)	Remarks / Basic Installation Guideline**
WPC Deck board	125(w) X 25 (thk.) X 3,050 (L) 138(w) X 22.5 (thk.) X 2,800 (L) 140(w) X 24 (thk.) X 2,800 (L) 150 (w) X 25 (thk.) X 2,800 (L)	Installed with expansion gaps (5- 10 mm)
HDPE-WPC Solid Batten	40 (w) X 25 (thk.) X 3,050 (L)	Running @ 250 mm c/c (max.). Optional battens material, i.e. grade A hard wood, gal. steel, aluminium, s/steel e.t.c.
Edging board	95 (w) X 10 (thk.) X 3,050 (L) or 63 (w) X 10 (thk.) X 2,800 (L)	Tighten with stainless steel tapping screws directly on panel surface every 300.00 mm span at max, with silicone bonding adhesive applied between back of panel with contact surface. (Bonding adhesives for outdoor use.)
WPC L-angle	25 X 25 X 3,050 (L)	Installed with "direct screwed method" on @ every 300 mm (max) plus bonding silicon adhesive (external use type).
SS 304 screws	# 8 X 25 mm (for metal h/sections) # 8 X 30 mm (for WPC or wood) # 10 x 63 mm (to install battens)	Custom screws with head coated in brown to minimize glare when installed on deck board, wood or steel batten.
Fastener clip	As per samples	Made with / from durable nylon material.

**Remarks / Basic installation Guideline – above stated are only applicable for installations at normal site condition, do contact us if need further advise.

A Customized Edging Design

We are committed to providing customized edging solution for you to meet all your design requirement, perfecting your work is our mission.

